


70M



General Description

Metal case packed Crystal filter based on monolithic technology.

Features

- Compact and light weight
- Stable temperature characteristics
- Outstanding vibration and shock resistant characteristics

Main applications

Wireless

Electrical characteristics

Type	Channel (kHz)	Poles	BW (dB) (kHz)	Stop BW (dB) (kHz)	Ripple (dB)	Insertion loss (dB)	Min. attenuation[dB]		Load (k Ω //pF)	Holder	Cc (pF)
							+500/ 1000	-200/ -1000			
70M7.5A	70	2	3 \pm 3.75	10 \pm 12.5	1.0	2.0	KHz 35	KHz 35	2000//0	UM1-3	
70M7.5B	70	4	3 \pm 3.75	30 \pm 12.5	1.0	4.0	70	75	1800//0	UM1-3X2	0.5
70M12A	70	2	3 \pm 6.0	15 \pm 22	1.0	2.0	35	35	2000// -0.4	UM1X3	
70M12B	70	4	3 \pm 6.0	30 \pm 25	1.0	3.0	70	75	2000// -0.2	UM1-3X2	0
70M15A	70	2	3 \pm 7.5	15 \pm 30	1.0	2.0	35	35	2000// -0.9	UM1-3	
70M15B	70	4	3 \pm 7.5	25 \pm 25	1.0	3.0	70	75	2000// -0.4	UM1-3X2	-0.5
70M20A	70	2	3 \pm 10	15 \pm 40	1.0	2.0	35	35	2500// -0.1	UM1-3	
70M20B	70	4	3 \pm 10	35 \pm 40	1.0	3.0	70	75	2500// -0.4	UM1-3X2	-1.0
70M30A	70	2	3 \pm 15	15 \pm 60	1.0	2.0	35	35	4000// -0.7	UM1-3	
70M30B	70	4	3 \pm 15	30 \pm 60	1.0	3.0	70	75	4000// -0.8	UM1-3X2	-1.1

Remark : specifications subject to change without prior notice. Please confirm with our sales

Dimensions

